



THERMODYNE
Enhancing Energy Efficiency

COMBITHERM ULTRA

Water-Cum-Smoke Tube Boiler



IBR
1950





Our Product Range



Technical Specifications

Boiler Type	Water-Cum-Smoke tube Type Boiler
Capacity Range	1 TPH - 10 TPH
Dryness fraction	98%
Boiler efficiency	82 ± 2%
Power Supply	AC, 3 Ph, 415V, 50 Hz, 4-Wire System
Fuel Options	All Biomass fuels, Rice husk, Briquettes, Coal, Agro-waste, Wood & Wood Chips
Model Options	Manual, Fluidised Bed Combustion, Automatic Feeding
Design code	IBR-1950 with Latest Amendments
Max. Working Pressure	10.54-28.12 Kg/cm ² (g)
Boiler Accessories	Air Pre-heater, ID fan, FD fan, Dust Collector, Feed Pump, Chimney, Combustion System, Mountings & Fittings



THERMODYNE ENGINEERING SYSTEMS

📍 A-7/110 SSGT Road Industrial Area, Ghaziabad, UP-201009 (INDIA)

📍 E-11 South East Zone MIA Alwar - Rajasthan-301030 (INDIA)

✉ sales@thermodyneboilers.com

🌐 www.thermodyneboilers.com

☎ +91 9990226006